

CT718 COMPOST TURNER



AGGRESSIVE FLAILS. The aggressive Vermeer flails ensure aeration and mixing. When properly aerated, the composting cycle is considerably shortened and site throughput is increased.




JOBSITE EFFICIENCY. Advanced Control System (ACS) controller monitors engine rpm and slows or stops the ground drive when it reaches the programmable set point to reduce stalling the turner in the windrow.



RELIABLE COMPONENTS. The poly-synchronous belt drum drive has proven to be a reliable system requiring little maintenance and offering adjustable shafts.



PRECISE CONTROL. Equipped with independently controlled lift cylinders for thorough aeration of the compost pile.



EXTENDED CLUTCH LIFE. Engine power is transferred through the hydraulically actuated PT Tech clutch. To help extend clutch life, control software prevents the operator from engaging or disengaging the drum drive at full engine rpm.



EASE OF MAINTENANCE. All grease points are accessible from ground level. Hinged, lockable doors on both sides of the engine provide spacious access for maintenance.

CT718 COMPOST TURNER

GENERAL DIMENSIONS

Max transport width: 27.7' (8.4 m)

Max transport length: 9.5" (24.1 cm)

Max transport height: 13.5' (4.1 m)

Max operational width: 27.7' (8.4 m)

Max operational length: 14' (4.3 m)

Max operational height: 19' (5.8 m)

Weight: 44,000 lb (19,958.1 kg)

Capacity: 5000 tons/hr (4536 metric tons/hr)

ENGINE

Model: Caterpillar C15 Tier 3

Number of cylinders: 6

Max gross horsepower: 540 hp (402.7 kW)

Fuel tank capacity: 155 gal (586.7 L)

HYDRAULIC SYSTEM

Tank capacity: 61 gal (230.9 L)

Filtration method: Return filter and suction strainer

FRAME

Mainframe: Constructed of 8" x 6" x .4" (20.3 cm x 15.2 cm x 1 cm) and 6" x 6" x .25" (15.2 cm x 15.2 cm x .6 cm) steel tube with continuous welding

OPERATING HEIGHT ADJUSTMENT

Operating height adjustment: The machine's operating height is adjusted on each front wheel with independently operated hydraulic cylinders and on the rear wheels with a pair of jointly operated hydraulic cylinders from 0 to 18" (0 to 45.7 cm) above ground.

GROUND DRIVE

Ground drive type: Standard 4-wheel drive system

Tire size: 48 L x 32.00-10, 12-ply floatation deep-tread traction tires

PROCESSING TUNNEL

Windrow width: 18' (5.5 m)

Windrow height: 7' (2.1 m)

Tunnel lining: Fully lined .25" (.6 cm) steel plate

Rubber skirting curtains (thickness): .4" (1 cm)

DRUM

Drum diameter (including flails): 44" (111.8 cm)

Number of flails: 102

Flail dimensions: .75" x 4" x 11.6" (1.9 cm x 10.2 cm x 29.5 cm)

Double roller main drum bearings: 6" (15.2 cm)

CAB

Width: 64" (162.6 cm)

Retraction: 15" (38.1 cm)

NOTES:

Vermeer Freeman Manufacturing, Inc. reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo and Equipped to Do More are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. © 2015 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

