

RTX200 PEDESTRIAN TRENCHER



ENHANCED VZ STEERING. Operators can steer the machine using only the handlebars — rather than traditional methods using levers or steering wheels. These bars also provide additional leverage when operating on difficult terrain.



DEPTH-CONTROL. Elimination of the tail wheel on the track unit provides trenching depth-control in uneven ground conditions and convenience to move through tight spaces.



HIGH-TORQUE DIGGING. The RTX200 is equipped with a 20.5 hp (15 kW) Kohler engine for optimal power on your jobsite.



SLENDER PROFILE. The 35" (88.9 cm) width allows the RTX200 to access compact spaces — including passing through typical backyard gates.



EASE OF MAINTENANCE. The hydraulic hoses and hard-line design provide convenient service and maintenance.



MASTER YOUR TERRAIN. Option of tracks or tires helps you attain maximum performance and productivity despite varying surface conditions.

RTX200 PEDESTRIAN TRENCHER

GENERAL WEIGHTS AND DIMENSIONS

Weight (basic tractor with tracks): 1170 lb (530.7 kg)

Weight (basic tractor with tires): 940 lb (426.4 kg)

Length (basic tractor with tracks): 73" (185.4 cm)

Length (basic tractor with tires): 83" (210.8 cm)

Width: 35" (88.9 cm)

Height: 46" (116.8 cm)

Wheel base: 33.2" (84.3 cm)

Tread width: 8.5" (21.6 cm)

TRENCHER

Digging depth: 36" (91.4 cm)

Cutting width: 4" – 6" (10.2 cm – 15.2 cm)

Auger diameter: 16" (40.6 cm)

Min transport length: 89" (226 cm)

ENGINE

Make/Model: Kohler CH640

Gross horsepower: 20.5 hp (15 kW)

Displacement: 41.1 cu-in (.67 L)

Fuel type: Gasoline

Fuel tank capacity: 1.6 gal (6.1 L)

Cooling medium: Forced air

Max operating angle (fore/aft)*: 25°

Max operating angle (left/right)*: 25°

Number of cylinders: 2

Aspiration: Natural

Engine oil capacity: .5 gal (1.9 L)

*Engine operating angles do not indicate safe machine operating angles.

NOTES:

HYDRAULIC SYSTEM

Hydraulic tank capacity: 10.75 gal (40.7 L)

Hydraulic system capacity: 11.25 gal (42.6 L)

Attachment pump flow at max engine rpm: 10.3 gpm (39.0 L/min)

Ground drive flow at max engine rpm: 5.4 gpm (20.4 L/min)

GROUND DRIVE

Ground drive type: Hydrostatic

Max forward transport speed at full throttle: 3.1 mph (5.0 km/h)

Max reverse transport speed at full throttle: 1 mph (1.6 km/h)

OPTIONS

Backfill blade

Trench cleaner

Extended warranty

Special paint

Planned maintenance

Vermeer Confidence Plus® asset protection program